

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) **UK Patent Application** (19) **GB** (11) **2 254 812 A** (13)
(43) Date of A publication 21.10.1992

(21) Application No 9108401.2

(22) Date of filing 19.04.1991

(71) Applicant
Minnesota Mining and Manufacturing Company

(Incorporated in the USA - Delaware)

**PO Box 33427, 3M Center, Saint Paul,
Minnesota 55144, United States of America**

(72) Inventor
Phillip A Mitchell

(74) Agent and/or Address for Service
**Lloyd Wise, Tregear & Co
Norman House, 105-109 Strand, London,
WC2R 0AE, United Kingdom**

(51) INT CL⁵
B05C 21/00


(52) UK CL (Edition K)
B2L LCVA

(56) Documents cited
None

(58) Field of search
**UK CL (Edition K) B2L
INT CL⁵ B05C 21/00**

(54) **Masking using flexible strip**

(57) A method of masking an area of a surface using a length of flexible foam strip having a layer of adhesive 20 and 22 applied on opposite sides of the strip. The strip is attached to the surface by one of the layers of adhesive and a sheet of material is attached to the opposite side of the strip by the other of the layers of adhesive. The strip and sheet then isolate the area of the surface from contiguous areas of the surface.



1/2




FIG. 4




FIG. 5




FIG. 1




FIG. 2




FIG. 3

MASKING METHODS USING FLEXIBLE STRIP

The present invention relates to methods for masking an exposed area of a surface from an adjacent area to facilitate treatment of the exposed area by for example paint spraying. The invention has particular, but not exclusive application in the motor industry where selective repairs must be effected on painted surfaces. The invention also relates to a gasketting material for use in such methods.

Various masking techniques are known for isolating areas from adjacent areas on a surface. Such isolation is needed in a number of situations where treatment of one form or another is to be applied exclusively to a specific area or region. Masking techniques are particularly useful when the treatment involves the application of a fluid medium. Examples are chemical treatments, painting and decorating. Typically, the treatment areas are isolated from their surroundings by a masking tape which defines the boundary thereof.

The present invention is directed at a masking technique in which the boundary of the treatment area is defined by a length of foam strip adhesively secured to the surface. The strip has a layer of adhesive applied on opposite sides thereof, whereby one layer secures the strip to the surface, and the other is available for attachment to a sheet of material. The sheet of material is attached in such a way that it extends laterally of the strip, protecting the surface adjacent that flank and leaving the surface adjacent the other flank exposed. With a sheet of material attached in this way, the strip and sheet thereby isolate an area of the surface from a contiguous area. The sheet of material can be attached to the foam strip with a substantial overlap, and the sheet of material trimmed thereafter before the surface area is treated.

The invention is also embodied in a length of foam strip having a layer of adhesive applied on opposite

sides thereof. In preferred embodiments, the adhesive forming one of the layers thereof is more aggressive than the adhesive forming the other layer, and the less aggressive adhesive layer is used to secure the strip to the surface. Thus, in use the more aggressive adhesive is preferentially adhered to the sheet of material, which facilitates the subsequent removal of the strip or mask from the surface. The strip may come in the form of an endless length, and in some embodiments can include a sheet of material secured to the strip by one of the adhesive layers.

In preferred embodiments of the invention, the cross-section of the foam strip has a periphery forming a continuous smooth curve. Normally, it will be circular or elliptical. This facilitates the formation of a soft edge between the treated and untreated areas.

The invention will now be further described by way of example, and with reference to the accompanying schematic drawings wherein:

Figure 1 illustrates a car door with lengths of gasketting material secured thereto;

Figure 2 is a section taken on line II-II of Figure 1;

Figure 3 is a perspective view showing gasketting material according to the invention drawn from a roll thereof.

Figure 4 is a perspective view of a part of a car hood; and

Figure 5 is a cross-section taken on line V-V of Figure 4.

Figure 1 is a side view of a car door with a surface area "X" thereof having been repaired, but not yet repainted. The car door is shown separated from the car body, but is otherwise intact with windows 2 and 4, and frame 6 fitted thereto, and door handle 8 and mirror mount 10 still in place. Additionally, at the bottom edge of the door is an extra protective layer 12.

Secured to the door panel 14 are two lengths of strip 16, 18 attached by adhesive to undamaged areas of the panel 14. The strips 16 and 18 define two boundaries of the repaired area "X", and thereby separate the repaired area "X" from the undamaged areas of the panel 14 on or in which are mounted auxiliary features (8, 10, and 12).

In Figure 1, the strips 16 and 18 are visible and as shown, merely form a divide between adjacent areas of the surface of panel 14. In use, sheets of material 24 would be applied to each strip, the respective sheets extending over the panel and auxiliary components to enable the area "X" to be treated; ie, in this example spray painted, to complete a repair. The disposition of such a sheet of material is shown in Figure 2. As can also be seen in Figure 3, the foam strip bears two separately identifiable layers 20 and 22 of adhesive. Adhesive layer 20 secures the strip 10 to the panel 14. A sheet 24 of flexible material is adhered along a marginal edge portion to the adhesive layer 22. The free edge of the sheet 24, on the right flank of the strip 18 as shown in Figure 2, can be trimmed so that the foam strip 18 is substantially visible from that side. On the left flank of the strip 18 as shown in Figure 2, the sheet 24 extends either freely or to a remote securement point which may be on the layer 12, but in any event in such a manner effectively to protect the panel 14 below the strip 18 in Figure 1 from any overspray directed at the area "X". The area above the strip 16 in Figure 1 would be similarly protected by the application of a sheet of material (not shown) to the strip 16. Suitable materials for the sheet 24 include paper, coated paper and plastics materials.

Figure 3 shows a foam strip embodying the invention drawn from a roll 26 thereof. The material of the strip will normally be a plastics foam, and is preferably one made in accordance with our published European Patent Specification No. 0384626. Polyether foam is particularly suitable. Various adhesives can be used for

the layers 20 and 22, and emulsion adhesives can be satisfactory. In any event, pressure sensitive adhesives are preferred to ensure that the strip can be properly located on the surface. A double sided release liner 28 attached to the adhesive layer 22 is shown peeled away to prepare the exposed length for use. The cross-section of the strip is typically circular or elliptical, with minimum diameters in the range of 15 to 20 mms being preferred.

The adhesive of one layer of the foam strip is normally more aggressive than that of the other. In the example illustrated, the layer 22 is the more aggressive adhesive, and the less aggressive layer 20 is the one that is applied to the panel surface. In order to enable the strip to be used in this manner, the adhesive layers can be distinguished from one another, normally by a visible difference such as colour. Alternatively, the adhesive layers may be applied to the strip in different patterns, and one or each layer may be discontinuous. Normally though, continuous layers are preferred.

In the embodiment of the invention described above, the area "X" of the panel 14 was isolated by the sequential application of the strips 16 and 18, and the sheets 24. This is the normal arrangement, and provides the greatest flexibility, but it will be appreciated that other techniques can be used. For example, it may be desirable to protect an isolated area of a panel from treatment, and such an arrangement is shown in Figures 4 and 5.

Figure 4 shows the front section of a car hood 30, most of which is to be re-painted. An emblem 32 is mounted on the hood 30, and as the paintwork around the emblem 32 does not require re-painting, this area of the hood is to be isolated from the remainder. To achieve this, a strip 34 of gasketting material according to the invention is applied in a continuous length around the emblem to the surface of the hood 30. This is shown more clearly in Figure 5. As can be seen, the strip 34

encloses the emblem 32, and a sheet 36 of material adhered to the strip 34 isolates the emblem and its immediate surroundings. It will be appreciated that the arrangement shown in Figure 5 is substantially the same as that shown in Figure 2, but with a single length of strip 34 firmly holding the sheet of material 36.

In some further embodiments, a masking unit may be provided with the sheet already adhesively secured to the foam strip. The sheet and strip can be wound on a roll, or provided as a ready made panel, as shown in Figure 5. Here, the sheet 36 is already adhered to the endless strip 34. It is then possible to isolate an area of the surface in a single exercise.

The technique described herein has particular benefit in paint repairs, as the foam strip greatly facilitates the achievement of a soft edge between painted and unpainted areas. The reason for this is that the circular or elliptical cross-section of the preferred foam strip, as shown for example in Figures 2, 3 and 5, avoids the definition of a sharp edge or boundary. The new paint is thus applied in a reducing thickness under the overhanging section of the strip to merge tidily with the contiguous unpainted area. The overhanging section can also be extended if required by the sheet 24 or 36. While paint repairs constitute a preferred application of the invention, the technique is also useful for other surface treatments such as coating, plating and phosphorising.

CLAIMS

1. A method of masking an area of a surface using a gasketting material in the form of a length of flexible foam strip having a layer of adhesive applied on opposite sides of the strip wherein the strip is attached to the surface by one of the layers of adhesive and a sheet of material is attached to the opposite side of the strip by the other of the layers of adhesive, the strip and sheet thereby isolating said area of the surface from a contiguous area of the surface.
2. A method according to Claim 1 including the step of trimming the sheet along one edge adjacent the strip.
3. A method according to Claim 1 wherein a marginal edge portion of the sheet of material is attached to said opposite side of the strip.
4. A method according to any preceding Claim wherein the adhesive forming one of said adhesive layers is less aggressive than the adhesive forming the other layer, and wherein the less aggressive layer attaches the strip to the surface.
5. A method according to any preceding Claim wherein the strip is attached to the surface in the form of a closed curve, thereby enclosing said area.
6. A method according to any preceding Claim wherein the cross-section of the foam strip has a periphery forming a continuous smooth curve.
7. A gasketting material in the form of a length of flexible foam strip having a layer of adhesive applied on opposite sides thereof.
8. A material according to Claim 7 wherein the adhesive forming one of said adhesive layers is more aggressive than the adhesive forming the other layer.
9. A material according to Claim 7 or Claim 8 in the form of an endless length of said strip.

10. A material according to Claim 9 including a sheet of material adhesively secured to the strip by one of said layers of adhesive.

11. A material according to any of Claims 7 to 9 wherein the adhesive layers are visibly distinguishable from each other.

12. A material according to Claim 10 wherein each layer of adhesive is a continuous coating.

13. A material according to any of Claims 7 to 12 wherein the cross-section of the foam strip has a periphery forming a continuous smooth curve.

14. A material according to Claim 13 wherein said periphery is one of circular or elliptical.

Relevant Technical fields

- (i) UK CI (Edition K) B2L
(ii) Int CL (Edition 5) B05C 21/00

Search Examiner

M ELLIOTT

Databases (see over)

- (i) UK Patent Office
(ii)

Date of Search

19 MAY 1992

Documents considered relevant following a search in respect of claims

1 AND 7 AT LEAST

Category (see over)	Identity of document and relevant passages	Relevant to claim(s)
	NONE	1 and 7 at least

Category	Identity of document and relevant passages	Relevant to claim(s)

Categories of documents

X: Document indicating lack of novelty or of inventive step.

Y: Document indicating lack of inventive step if combined with one or more other documents of the same category.

A: Document indicating technological background and/or state of the art.

P: Document published on or after the declared priority date but before the filing date of the present application.

E: Patent document published on or after, but with priority date earlier than, the filing date of the present application.

&: Member of the same patent family, corresponding document.

Databases: The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).